

# LED EXIT SIGN

## Thermoplastic LED Exit Sign



### FEATURES & SPECIFICATIONS

#### Construction

- Injection-molded thermoplastic ABS housing UL-94V-0 flame rating - Flame Retardant, high temperature, thermoplastic hosing
- Universal design includes two faceplates, one backplate, and mounting canopy
- All configurations include field-selectable directional chevrons
- Standard finish: White

#### Optical System

- High intensity switchable red or green text options.
- Fully-illuminated 6" characters with 3/4" stroke
- Double Face Configuration

#### Electrical

- Standard Universal Voltage - 120/277VAC Dual Voltage Operation
- LED Indicator Light & Push Button Test Switch
- Power Draw (W): 2.4
- Test button to provide manual verification of the transfer circuit.

#### Battery

- Maintenance free AA Type, NiCad Battery
- Operating Temperatures 0°C to 40°C (32°F to 104°F)

#### Installation

- Easy snap together design for effortless installation

- Includes mounting canopy for wall and ceiling mount applications

#### Warranty

- 2 year warranty on all electronics and housing
- Separate 2 year pro-rated warranty on the battery

#### Listings

- UL 924
- UL listed for damp locations (20 °C -40 °C)
- 90 minute emergency run time, 24 hour recharge time

### ORDERING GUIDE

TYPICAL ORDER EXAMPLE:	<b>BRT EM EXT MC WH UNV</b>
------------------------	-----------------------------

Prefix	Letter Color	# of Faces	Housing Color	Lamp Heads	Options
<b>BRT-EM-EXT</b> Thermoplastic Exit Sign	<b>MC - Multicolor</b>	<b>U - Universal</b> (includes two face plates, back plate, and mounting canopy)	<b>WH - White</b>	<b>N/A</b>	

### PRODUCT DIMENSIONS

