

FEATURE

- Injection-molded thermoplastic ABS housing and polycarbonate cover, UL 94V-0 flame rating.
- Innovative, easy installation in minutes
- Letters 6" height with 3/4" stroke. Optional RED or GREEN letters.
- Universal J-box mounting pattern
- 120V/277VAC Dual voltage operation
- Single or double face(Universal).
- Built-in 3.6V500mAh Ni-Mh battery for minimum 90 minutes emergency operation.(JLWPEEW)
- Built-in 3.6V1200mAh Ni-Mh battery for minimum 90 minutes emergency operation.(JLWPECW)
- Maximum 24 hours for full recharge time
- Test switch and charge indicator
- UL and cULus Wet location listed
- -20° to 40°C outdoor damp location listed

ORDERING INFORMATION

FAMILY	TYPE	FACEPLATE	LENS	HOUSING COLOR	WET LOCATION
BRT-EM-EX-OT-R-UNV-GRAY	EE(SIGN ONLY)	1(DOUBLE)	R(RED)	W(WHITE)	WP(WATERPROOF)
BRT-EM-EX-OT-R-UNV-GRAY	EC(WITH TWO LAMP HEADS)	2(DOUBLE)	G(GREEN)	B(BLACK)	WP(WATERPROOF)



PACKING INFORMATION

MODEL NO.	PACKING INFORMATION	WEIGHTS
BRT-EM-EX-OT-R-UNV-GRAY	44x35x24cm/6pcs	12/11kgs
BRT-EM-EX-OT-R-UNV-GRAY	44x35x24cm/6pcs	12/11kgs
BRT-EM-EX-OT-R-UNV-GRAY	44x35x24cm/6pcs	13/12kgs
BRT-EM-EX-OT-R-UNV-GRAY	44x35x24cm/6pcs	13/12kgs
BRT-EM-CMB-OT-R-UNV-GRAY	44x35x38cm/6pcs	16.0/15.0kgs
BRT-EM-CMB-OT-R-UNV-GRAY	44x35x38cm/6pcs	16.0/15.0kgs
BRT-EM-CMB-OT-R-UNV-GRAY	44x35x38cm/6pcs	17.0/16.0kgs
BRT-EM-CMB-OT-R-UNV-GRAY	44x35x38cm/6pcs	17.0/16.0kgs

FAMILY: BRT-EM-EX-OT-R-UNV-GRAY
BRT-EM-CMB-OT-R-UNV-GRAY

NOTES: IP65 Waterproof, Suitable for outdoor & wet location,
UL & cUL Listed

TYPE: WET LOCATION LED EMERGENCY EXIT/COMBO



WET LOCATION LED EMERGENCY EXIT/COMBO

BRT-EM-EX-OT-R-UNV-GRAY

BRT-EM-CMB-OT-R-UNV-

ELECTRICAL INFORMATION							
MODEL	RATED VOLTAGE	INPUT CURRENT	INPUT WATT	LED TYPE	CHARGING TIME	EMERGENCY RUN TIME	IP GRADE
BRT-EM-EX	120/277V	0.026-0.015A	2.90-3.59W	10Pcs Red LEDs	24 Hrs	180 Mins	IP 65
BRT-EM-EX	120/277V	0.025-0.014A	2.74-3.51W	6Pcs Green LEDs	24 Hrs	180 Mins	IP 65
BRT-EM-EX	120/277V	0.026-0.015A	2.90-3.59W	10Pcs Red LEDs	24 Hrs	180 Mins	IP 65
BRT-EM-EX	120/277V	0.025-0.014A	2.74-3.51W	6Pcs Green LEDs	24 Hrs	180 Mins	IP 65
BRT-EM-CMB	120/277V	0.025-0.016A	2.90-3.79W	10Pcs Red LEDs+2.4W LED Lamp assombly	24 Hrs	90 Mins	IP 65
BRT-EM-CMB	120/277V	0.026-0.014A	2.94-3.49W	6Pcs Green LEDs+2.4W LED Lamp assombly	24 Hrs	90 Mins	IP 65
BRT-EM-CMB	120/277V	0.025-0.016A	2.90-3.79W	10Pcs Red LEDs+2.4W LED Lamp assombly	24 Hrs	90 Mins	IP 65
BRT-EM-CMB	120/277V	0.026-0.014A	2.94-3.49W	6Pcs Green LEDs+2.4W LED Lamp assombly	24 Hrs	90 Mins	IP 65

WET LOCATION LED EMERGENCY EXIT/COMBO

BRT-EM-EX-OT-R-UNV-GRAY
BRT-EM-CMB-OT-R-UNV-