

# LED OUTDOOR EMERGENCY

## Compact Wet Location Emergency Light



### FEATURES & SPECIFICATIONS

#### Construction

- Injection-molded UL 94 V-0 flame retardant, thermoplastic housing
- For outdoor use
- 12 high output LEDs per head with a fully gasket enclosure and clean polycarbonate lens cover.
- Standard finish: White

#### Optical

- Dual adjustable LED lamps with a beam angle of 36°

#### Electrical

- Standard Universal Voltage - 120/277VAC dual primary at 60Hz
- Test button to provide manual verification of the transfer circuit and emergency lamps

- Charge rate/power "ON" LED indicator Light and push-to-test switch for mandated code compliance testing.
- LVD - Low voltage disconnect eliminates deep discharge
- Solid-state transfer detects loss of line voltage and automatically switches to emergency mode
- Test button to provide manual verification of the transfer circuit and emergency lamps

#### Battery

- Maintenance free NiCad Battery
- Operating Temperature 0°C to 40°C (32°F to 104°F)

#### Installation

- Universal J-box mounting pattern with keyhole slots for ceiling and wall mounting

#### Warranty

- 2 year warranty on all electronics and housing.
- Separate 2 year pro-rated warranty on the battery.

#### Listings

- UL 924 Wet Location
- NFPA 101 Life Safety Code
- NEC
- OSHA
- Local and State Codes.
- UL Listed 90 minute emergency run time, 24 hour recharge time

### ORDERING GUIDE

TYPICAL ORDER EXAMPLE: **BRT EM OT WH UNV**

Prefix	Housing Color	Options
<b>BRT-EM-OT</b> - Compact Wet Location Emergency Light	<b>WH</b> - White <b>BK</b> - Black <b>GY</b> - Gray	

### PRODUCT DIMENSIONS

